

3.6 Table of concordance of components

* (410) * (430)

Number	5601	5602	Designation
100	xx	xx	Plate
105	*	xx	Barrel bridge
110	xx		Train bridge
110		xx	Train bridge
121/3	xx	xx	Balance cock
125	xx	xx	Pallet cock
180/1	xx	xx	Barrel, complete (with mainspring)
201	*	xx	Center wheel
203	*	xx	Intermediate wheel
210	*	xx	Third wheel
220	*	xx	Fourth wheel
240	*	xx	Cannon pinion
250	*	xx	Hour wheel
260	*	xx	Minute wheel
307	xx	xx	Triovis device, complete
324	xx	xx	Incabloc, jeweled, upper
325	xx	xx	Incabloc, jeweled, lower
401	*	xx	Winding-stem
404	*	xx	Stem for waterproof case
407	*	xx	Clutch wheel
410	*	xx	Winding-pinion
415	*	xx	Ratchet wheel
420	*	xx	Crown wheel
423	*	xx	Crown-wheel core
425	*	xx	Click
430	*	xx	Click spring
435	*	xx	Yoke (clutch lever)
440	*	xx	Yoke spring (set spring)
443	*	xx	Setting-lever (detent)
445	*	xx	Setting-lever spring (set bridge)
450	*	xx	Setting-wheel
705	*	xx	Escape wheel
710	*	xx	Jeweled pallet fork and staff
721	xx	xx	Balance with flat hairspring, regulated
920	*	xx	Protecting-sleeve
963	*	xx	Stem for waterproof crown
5105	xx	xx	Barrel-bridge screw
5110	xx	xx	Train bridge screw
5121/3	xx	xx	Balance-cock screw
5125	xx	xx	Pallet-cock screw
5415	xx	xx	Ratchet-wheel screw
5423	*	xx	Screw for crown-wheel core
5425	xx	xx	Click screw
5445	*	xx	Screw for setting-lever spring
5738	xx	xx	Hairspring-stud screw
5750	*	xx	Dial screw

N.B.: Parts marked with an asterisk * are identical with those of caliber 410 - 430.

ONLY NOW AVAILABLE WITH 121/3 (COMPLETE COOL ASS'Y)

100	105	110	121/3	125	180/1	201	203	210	220	240				
250	260	307	324	325	401	404	407	410	415	420	423	425	430	435
440	443	445	705	710	721	590086	920	963						
106075 (5105) (5110) (5121/3)	106066 (5125)	105063 (5415)	105034 (5423)	106067 (5425)	107013 (5445)	103502 104039 (5738)	107041 (5750)							