

## Calibre 1065M & 1080

Base Calibre 1030

- Ø28.50mm
- Train: 18.000
- Automatic
- Anti-magnetic
- Sweep second
- Shock Proof

1 : 1



7080



7081



7122



7127



7170



7172



7176



7178




7179



7180



7181



7182

2 : 1



7173



7174



7177

/



7183

1036	<b>7080</b>	<i>Center wheel with cannon pinion</i>
1036	<b>7081</b>	<i>Cannon pinion, height 2,65 mm</i>
1040	<b>7122</b>	<i>Balance cock</i>
1040	<b>7127</b>	<i>« Rolex Shock-resisting » device for balance, upper</i>
1066 M	<b>7170</b>	<i>Hour wheel, height 1,70 mm</i>
	<b>7172</b>	<i>Balance with Breguet hairspring, regulated</i>
1066 M	<b>7173</b>	<i>Screw for : Balance</i>
1066 M	<b>7174</b>	<i>Screw for : Regulating the balance</i>
1066 M	<b>7176</b>	<i>Stud</i>
1066 M	<b>7177</b>	<i>Screw for : Stud</i>
1066 M	<b>7178</b>	<i>Roller complete</i>
	<b>7179</b>	<i>Bridge for self-winding mechanism, 1065 M</i>
	<b>7180</b>	<i>Bridge for self-winding mechanism, 1080</i>
1066 M	<b>7181</b>	<i>Anti-magnetic ring</i>
1066 M	<b>7182</b>	<i>Anti-magnetic back</i>
	<b>7183</b>	<i>Set of screws for 1 watch movement</i>