

Calibre 1225

Ø23.80mm

Ht: 5.07mm

Train: 21.600

- Centre second
- Calendar
- Shock Proof
- 17 Jewels

Base Calibre 1210








Image	Rolex No.	Description
	7590	Centre wheel with cannon pinion
	7591	Cannon pinion
	7592	Hour wheel with double tothing
	7593	Driving wheel for date indicator
	7594	Screw for driving wheel for date indicator
	7595	Date jumper
	7596	Date star









Image	Rolex No.	Description
	7598	Date indicator seating
	7599-1	Date indicator • champagne
	7599-2	• silvered
	7599-14	• champagne red, black
	7600-2	Date indicator silvered
	7602	Screw for dial
	7619	Main plate
 	7620	Second wheel
	7621	Escape wheel

















Image	Rolex No.	Description
	7622	Pallet fork
	7623	Balance bridge
	7625	Balance with flat hairspring, timed
	7626-1	Inertia-block, gilt
	7626-2	Inertia-block, nickel-plated
	7627-1	Adjusting washer: 1/100
	7627-2	2/100
	7627-3	3/100
	7627-4	4/100
	7627-5	5/100
	7631	Balance staff
	7632	Regulator
	7633	Stud support
	7634	Regulating stud
	7635	Mainspring, strength standard
	7635-1	Mainspring, strength weak

Image	Rolex No.	Description
	7636	Shock-absorber for balance-upper
	7640	Set of screws
	7931	Shock-absorber for balance-lower
	55051	Screw for stud
	55128	Screw for date jumper
	95014-4	Spring for in-setting for balance-upper /lower